



PLATINUM ACCESS SYSTEMS, INC.

BLSW1016

COMMERCIAL SWINGER

The **BLSW1016** with its ultra-quiet high torque brushless DC motor is the first choice for Residential/Commercial applications. This full features state of the art operator uses a 120/220VAC single phase main power source and utilizes a high efficient switching power supply to supply the proper voltage for operation. The operator is equipped with a built-in 24VDC battery backup system and it can operate with a direct solar panel connection as well.

This operator is designed to operate in any climate; it does not require a gearbox or a battery heater to operate in -20°F. Temperature between -20°F and -40°F require a battery heater and below -40°F it requires a gearbox heater as well.



These unique engineering innovations backed by the safety and reliability of the most advanced control board in the industry ensure a smooth operation for any Platinum Access Systems' operator.

Specification	Data	Specification	Data
Manual Release	Release Handle/Back Drivable Optional Fail Safety	Dimensions	15"x 17.5"x 24"H
Gate Capacity	Maximum Gate Weight: Length: 1000 lbs. 16' 1600 lbs. 12' 90° Opening in 13-18 Seconds (Max @ 120°)	Main Power	120/220 VAC Single Phase On/Off Switch Built-in 24V DC Battery Backup (7AmpHr 12V DC X 2)
Mechanical	Gear Reducer Size 70	Compliance	ETL Listed UL325/UL991
Motor	Brushless Continuous Duty Instant Reversing 24V DC	Warranty	Brushless Motor: Residential Commercial Parts: 10yrs. 8yrs. 8yrs. 6yrs.



PLATINUM ACCESS SYSTEMS, INC.

BLSW1016

COMMERCIAL SWINGER

FEATURES AND BENEFITS:

- **Dynamic Speed Control – No speed variation when gate load changes and power switches between AC and battery. Slider works on slope without coasting.**
- **Automatic Learning With Self Sync – Automatically synchronizes gates with different travel times for primary/secondary gate installation.**
- **Solar Priority Power Supply – With a larger solar panel, the gate will run on the solar panel instead of the batteries when the sun light is sufficient, saving battery life.**
- **Soft Start and Soft Stop – Minimizes wear on the gate system that significantly helps the gate last longer.**
- **High Efficiency Brushless Motor – For smooth, high torque and maintenance free operation.**
- **Solid State Motor Drivers – For quiet and long lasting operation**
- **Advanced Maglock Control – Engage maglock before or after gate is closed. Maglock works at both gate open and close position.**
- **Dual Output Loop Detector Rack – Type “B” relays on loop detector can be used for additional features.**
- **Individual Alarm For Primary/Secondary Installation – Alarm sounds from individual operator, automatically indicates the obstructed gate.**
- **Motor Brake and Maglock Release by FIRE/KEY Input – Enables manual gate operation in emergency.**
- **One Controlled Power Supply Output for Photo Beam Detector – In solar installation, turns off PBD when the gate is closed to save battery life.**
- **High Capacity DC Back Up – Over 100 cycles on DC back up depending on models and gate sizes.**
- **Adjustable Leaf Delay – Delay on either leaf from the primary unit.**
- **Stackable Limit Switches – For additional features.**
- **Fail Safe/Secure Capability – Be able to set to fail secure, fail safe or open on power fail.**
- **Heavy Duty Chassis – Corrosion resistant powder coated chassis.**
- **BLGOC-2200 control board with input/output LED's.**
- **Electronic reversing sensor built into control board.**
- **Adjustable timer from 0-60 seconds.**
- **Surge protection.**
- **Alarm reset button.**
- **Weatherproof polyethylene clam shell cover.**

PLATINUM ACCESS SYSTEMS, INC.

1725 E. Grevillea Court, Ontario, CA 91761 | Sales: (909) 259-6005 | Fax: (909) 923-7890 | www.platinumasi.com

Technical Support (909) 259-6001 | Email: sales@platinumasi.com | techsupport@platinumasi.com